



# GRIP JACK SUSPENSION CANOPIES WITH POWER SUPPLIES FOR 24VDC STATIC WHITE AND WARM DIM LEDs

REV.01.08.18



ASSEMBLED IN THE USA

## GRIP JACK SUSPENSION CANOPIES WITH POWER SUPPLIES

ORDERING CODES	GSP-RM-2RD-1P-50-ELV-__ GSP-RM-2SQ-1P-50-ELV-__	GSP-NC-2RD-1P-50-ELV-__ GSP-NC-2RD-1P-50-ELV-__	GSP-4RD-1P-50-ELV-__ GSP-4SQ-1P-50-ELV-__	GSP-5SQ-1P-60-ELV-__	GSP-5SQ-2P-2X60-ELV-__
SPECIFICATIONS					
DESCRIPTION	Grip Jack Suspension 2.68" canopy with Remodel Plaster Plate and 50W power supply that fits in junction box with 1-port power feed	Grip Jack Suspension 2.68" canopy with New Construction 2" Plaster Ring and 50 watt power supply that fits in junction box, with 1-port power feed	Grip Jack Suspension canopy with Remodel 4.6" canopy and 50 watt power supply that fits in existing junction box with 1-port power feed	2x60W Grip Jack Suspension 5" square Surface Mount canopy with 1-port feed	2x60W Grip Jack Suspension 5" square Surface Mount canopy with 2-port feed
MAXIMUM LOAD	60W-NON IC, 50W-IC (FITS IN JBOX)	60W-NON IC, 50W-IC (FITS IN JBOX)	60W-NON IC, 50W-IC (FITS IN JBOX)	60W	2X60W
INPUT VOLTAGE	120VAC	120VAC	120VAC	120VAC	120VAC
OUTPUT VOLTAGE	24VDC	24VDC	24VDC	24VDC	24VDC
DIMENSIONS	2.68" x 2.68" x .1"	2.68" x 2.68" x .1"	4.6" x 4.6" x .2"	5.5" X 5.5" X 1.5"	5.5" X 5.5" X 1.5"
FINISH	BK, CH, SN, WH	BK, CH, SN, WH	BK, CH, SN, WH	BK, CH, SN, WH	BK, CH, SN, WH
CLASSIFICATION	CLASS 2	CLASS 2	CLASS 2	CLASS 2	CLASS 2
MOUNTING	REMODEL CONSTRUCTION, POWER SUPPLY RECESSED IN JBOX	NEW CONSTRUCTION, POWER SUPPLY RECESSED IN JBOX	REMODEL CONSTRUCTION POWER SUPPLY RECESSED IN JBOX	SURFACE MOUNT	SURFACE MOUNT
EFFICIENCY	85%	85%	85%	85%	85%
SHORT CIRCUIT PROTECTION	YES	YES	YES	YES	YES
OVER TEMPERATURE PROTECTION	YES	YES	YES	YES	YES
WORKING TEMPERATURE	-30°C TO 90°C	-30°C TO 90°C	-30°C TO 90°C	-30°C TO 90°C	-30°C TO 90°C
DIMMING AND CONTROLS					
LUTRON DIVA: DVELV-300P	•	•	•	•	•
LUTRON SKYLARK: SELV-300P	•	•	•	•	•
LUTRON RADIO RA2: RRD-6NA	N/A	N/A	N/A	•	•
LUTRON MAESTRO: MAELV-600	•	•	•	•	•
LEGRAND ADORNE: ADTP-703TUM4	N/A	N/A	N/A	•	•

## GRIP JACK SUSPENSION CANOPIES WITH POWER SUPPLIES

ORDERING CODES	GSP-5SQ-1DP-2X60-ELV-__	GSP-6SQ-1P-100-ELV-__ GSP-6SQ-1P-150-ELV-__	GSP-6SQ-2P-2X100-ELV-__ GSP-6SQ-2P-2X150-ELV-__	GSP-6SQ-1DP-2X100-ELV-__ GSP-6SQ-1DP-2X150-ELV-__	GSP-6SQ-1P-200-ELV-__
SPECIFICATIONS					
DESCRIPTION	2x60W Grip Jack Suspension 5" square Surface Mount canopy with 2-port feed used with Nova Up/Down	100W or 150W Grip Jack Suspension 6" square Surface Mount canopy with 1-Port feed	2x100W or 2X150W Grip Jack Suspension 6" square Surface Mount canopy with 2-Port feed	2x100W or 2X150W Grip Jack Suspension 6" square Surface Mount canopy with Dual-Port feed	200W Grip Jack Suspension 6" square Surface Mount canopy with 1-Port feed
MAXIMUM LOAD	2X60W	100W OR 150W	2X100W OR 2X150W	2X100W OR 2X150W	200W
INPUT VOLTAGE	120VAC	120VAC	120VAC	120VAC	120VAC
OUTPUT VOLTAGE	24VDC	24VDC	24VDC	24VDC	24VDC
DIMENSIONS	5.5" X 5.5" X 1.5"	6.5" X 6.5" X 1.875"	6.5" X 6.5" X 1.875"	6.5" X 6.5" X 1.875"	6.5" X 6.5" X 1.875"
FINISH	BK, CH, SN, WH	BK, CH, SN, WH	BK, CH, SN, WH	BK, CH, SN, WH	BK, CH, SN, WH
CLASSIFICATION	CLASS 2	100W CLASS 2 150W UL2108	100W CLASS 2 150W UL2108	100W CLASS 2 150W UL2108	UL2108
MOUNTING	SURFACE MOUNT	SURFACE MOUNT	SURFACE MOUNT	SURFACE MOUNT	SURFACE MOUNT
EFFICIENCY	85%	85%	85%	85%	85%
SHORT CIRCUIT PROTECTION	YES	YES	YES	YES	YES
OVER TEMPERATURE PROTECTION	YES	YES	YES	YES	YES
WORKING TEMPERATURE	-30°C TO 90°C	-30°C TO 90°C	-30°C TO 90°C	-30°C TO 90°C	-30°C TO 90°C
DIMMING AND CONTROLS					
LUTRON DIVA: DVELV-300P	•	•	•	•	•
LUTRON SKYLARK: SELV-300P	•	•	•	•	•
LUTRON RADIO RA2: RRD-6NA	•	•	•	•	•
LUTRON MAESTRO: MAELV-600	•	•	•	•	•
LEGRAND ADORNE: ADTP-703TUM4	•	•	•	•	•

PROJECT		FIXTURE TYPE		DATE	
---------	--	--------------	--	------	--